



PLUG, IN POLYAMIDE PA6, PG PITCH, IP54



Features

TECHNICAL INFORMATION

Minimum operating temperature	-20 °C
Maximum operating temperature	90 °C
Threshold of operating temperature for short periods	110 °C
Ingress Protection	IP54
Reference standard	DIN 40430; DIN 46320
Self-extinguishing fire class according to UL 94	HB

MATERIAL COMPOSITION AND TREATMENTS


Material	Polyamide 6
Halogen free	No

LOGISTIC

Customs code	39269097
--------------	----------

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Plug for cable screw gland [EC000032]
--------------	---------------------------------------



type	P	Markings found	Color	C [mm]	Fixing hole diameter [mm]	Width [mm]	H [mm]	Gross weight [g]	Type of packaging	Unit in minimal packaging [pcs]	Unit in standard packaging [pcs]	Minimum order quantity [pcs]
1052007	Pg7	factory mark; thread type	Grey RAL 7035	6	12.7	15	8	0,901	; box		100	100
1052007N	Pg7	factory mark; thread type	Black RAL 9005	6	12.7	15	8	0,904	; box		100	100
1052009	Pg9	factory mark; thread type	Grey RAL 7035	6	15.5	19	9	1,633	; box		100	100
1052009N	Pg9	factory mark; thread type	Black RAL 9005	6	15.5	19	9	1,680	; box		100	100
1052011	Pg11		Grey RAL 7035	7	18.8	22		2,240	; box		100	100
1052011N	Pg11		Black RAL 9005	7	18.8	22		2,170	; box		100	100
1052013	Pg13,5		Grey RAL 7035	7	20.5	25		2,760	; box		100	100
1052013N	Pg13,5		Black RAL 9005	7	20.5	25		2,740	; box		100	100
1052016	Pg16		Grey RAL 7035	7	22.6	27		3,120	; box		100	100
1052016N	Pg16		Black RAL 9005	7	22.6	27		3,075	; box		100	100
1052021	Pg21		Grey RAL 7035	9	28.5	33		4,650	; box		50	50
1052021N	Pg21		Black RAL 9005	9	28.5	33		4,582	; box		50	50
1052029	Pg29		Grey RAL 7035	9	37.2	44		9,947	; box	25	100	25
1052029N	Pg29		Black RAL 9005	9	37.2	44				50		50
1052036	Pg32	factory mark; thread type	Grey RAL 7035	10	47.2	55	15	14,800	; box		20	20
1052036N	Pg32	factory mark; thread type	Black RAL 9005	10	47.2	55	15	14,400	; box		20	20
1052042	Pg42	factory mark; thread type	Grey RAL 7035	10	54.2	62	16	19,800	; box		10	10
1052042N	Pg42	factory mark; thread type	Black RAL 9005	10	54.2	62	16		; box		10	10
1052048	Pg48	factory mark; thread type	Grey RAL 7035	12	60	69	18	25,400	; box		10	10
1052048N	Pg48	factory mark; thread type	Black RAL 9005	12	60	69	18	25,800	; box		10	10