



Main

Range of product	Acti 9
Device short name	MIN
Product or component type	Electromechanical timer
Colour tint	White(RAL 9003)

Complementary

Device application	Building
Load type	Serial-corrected fluorescent tube, balast : conventional, (2300 VA) Parallel-corrected fluorescent tube, balast : conventional, (1300 VA) Non-corrected fluorescent tube, balast : conventional, (2300 VA) Fluorescent tube, balast : electronic, (300 VA) Fluocompact lamp, balast : conventional, (2000 VA) Dual mounted fluorescent tube, balast : conventional, (2300 VA) 9 fluorescent lamp, balast : electronic, (7 W) 6 fluorescent lamp, balast : electronic, (11 W) 5 fluorescent lamp, balast : electronic, (20 W) 5 fluorescent lamp, balast : electronic, (15 W) 230 V AC incandescent lamp, (2300 W) 230 V AC halogen lamp, (2300 W)
Power consumption	1 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V (- 10...15 %) AC 50 Hz
Time delay	Adjustable from 1 to 7 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals : <= 6 mm²
Width	18 mm
Height	83 mm
Depth	68 mm
Product weight	84 g

Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP20 B

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0620 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - go to CaP for more details
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual

Contractual warranty

Period	18 months
--------	-----------