



# 346338

**WATERTIGHT STRAIGHT SOCKET 3P+E 63A 380V 6H IP67**

| Registry                                                                                                                                                                                |               | Technical data            |               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------------------------|---------------|
| Net weight                                                                                                                                                                              | 1,359         | Frequency                 | 50-60Hz       |
| Min order quantity                                                                                                                                                                      | 1             | Protection level          | IP67          |
| EAN Code                                                                                                                                                                                | 8014950300921 | Poles                     | 3P+⏏          |
| <b>Reference Standards</b><br>EN 60309-1/A1: 2007<br>EN 60309-1/A1EC: 2014<br>EN 60309-1/A2: 2012<br>EN 60309-1: 1999<br>EN 60309-2/A1: 2007<br>EN 60309-2/A2: 2012<br>EN 60309-2: 1999 |               | Clock Position            | 6             |
|                                                                                                                                                                                         |               | Standard plug-socket      | EN60309-2     |
|                                                                                                                                                                                         |               | Nominal Operating Voltage | 400V          |
|                                                                                                                                                                                         |               | Insulating Voltage        | 500V          |
|                                                                                                                                                                                         |               | Manufacturing Material    | Thermoplastic |
|                                                                                                                                                                                         |               | Nominal current           | 63A           |
|                                                                                                                                                                                         |               | Execution                 | MOBILE        |
| <b>Marks</b>                                                                                                                                                                            |               | Shape                     | Straight      |
|                                                                                                        |               | <b>Attachments</b>        |               |
| Download EC Declaration of Conformity                                                                                                                                                   |               | DXF drawing               |               |