



# 69 Glass Cloth Electrical Tape - OEM

## Data Sheet

### Product Description

3M™ 69 Glass Cloth Electrical Tape is a white glass cloth tape with a high-temperature thermosetting silicone adhesive. The thermosetting adhesive provides an increased bond once applied in areas of high ambient temperatures. 69 Tape is UL recognized for continuous use up to 200°C. It conforms to Military Specification No. MIL-I-19166C.

### Applications

- Insulating electric and induction type furnace power supply leads
- Securing high temperature, non-PSA insulations (such as asbestos and glass) in high temperature areas
- Securing Scotch 77 Fire Retardant Electric Arc Proofing Tape
- Replacing 3M 27 Glass Cloth Electrical Tape in locations where a higher-temperature tape is needed
- Reinsulating and repairing coils on mining machines
- Reinforcing insulation in electrical installations where heavy loads cause high heat and breakdown of original insulation (e.g. motor control exciter feeds)
- Splicing silicone-covered glass wire where splices require more abrasion resistance and mechanical strength than can be provided by silicone tapes
- Insulating Class “H” dry-type transformer leads

### Typical Properties

Property	Value*
Thickness <sup>1</sup>	7.0 mils (.177 mm)
Tensile Strength <sup>1</sup>	180 lbs./in (314 N/10mm)
Elongation at Break <sup>1</sup>	5%
Adhesion <sup>1</sup>	40 oz/in (4.4 N/10mm)
Electrical Strength <sup>1</sup>	3000V
Insulation Resistance <sup>1</sup>	4.8 x 10 <sup>7</sup> (megohms)
Electrolytic Corrosion Factor <sup>2</sup>	0.9
Functional for Life of Component	200°C

\*Not recommended for specification purposes. Product specifications will be provided upon request.

Test Methods: <sup>1</sup> ASTM D-1000  
<sup>2</sup> 3M Test Method

3M is a trademark of 3M.

**Important Notice to Purchaser:**

All statements, technical information, and recommendations related to Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized office of Seller. The statements contained herein are made in lieu of all warranties, expressed or implied,

including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OF FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS.



**Electrical Products Division**

6801 River Place Blvd  
Austin, TX 78726-9000  
800-676-8381  
<http://www.3M.com/elpd>

© 3M 1998  
78-8124-4850-0(A)