



JUNCTION BOX

HP 100-L



HP 100-L

Junction box

113 x 113 x 58 mm

Article number: 32690001

Junction box acc. DIN EN 60670 (VDE 0606), $U_i=690V$, 7 recessed stepped nipples, seal range 5 - 21 mm, for terminals up to 10 mm²

grey, without terminals

IP55

IK07



690V
AC

Technical data

Measures

Width:	113 mm
Length:	113 mm
Height:	58 mm
Inner height:	32 mm
Inner width:	103.5 mm

Material

Base:	polypropylene, flame-retardant
Cover:	polypropylene, flame-retardant

Other attributes

Equipment:	None
Entries:	11
Rated cross section:	10 mm ²

Certificates



Accessory

KVR M25-MGM

KVR M20-GDB/MGM

VST M25-or

VST M20-or

AST M25-or

AST M20-or

DMS M25

KVR M20-MGM

DMS M20

AST M25

AST M20

KVR M25

KVR M20-GDB



JUNCTION BOX

HP 100-L

Tackable:	No
Rated insulation voltage AC:	690 V
Explosion safety:	none
Fire protection:	none
sealable:	No
Weatherproof:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP55 - acc. EN 60529 / DIN VDE 0470-1

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%

KVR M20

GMU PA M25

GMU PA M20

ADR M25

ADR M20

WST M25

WST M20

WNI M25

WNI M20

VST M25

VST M20

VSS PA M25

VSS PA M20

SNI M25

SNI M20

BST M20

KS M25