



JUNCTION BOX

HP 150-L

HP 150-L

Junction box

164 x 119 x 77 mm

Article number: 32695001

Junction box, Ui=690V, 10 recessed stepped nipples, seal range 5 - 21 mm

grey, without terminals



Technical data

Measures

Width:	164 mm
Length:	119 mm
Height:	77 mm
Inner height:	70 mm
Inner width:	155 mm

Material

Base:	polypropylene, flame-retardent
Cover:	polypropylene, flame-retardent

Other attributes

Equipment:	None
Entries:	11
Tackable:	No

Accessory

KVR M25-MGM

AST M25

KVR M25

GMU PA M25

ADR M25

WST M25

WNI M25

VST M25

VSS PA M25

SNI M25

KS M25

RST M25

WST M25/sw

WNI M25/sw

DMS M25/sw

VST M25-or

AST M25-or



JUNCTION BOX

HP 150-L

Rated insulation voltage AC:	690 V	DMS M25
Explosion safety:	none	KVR M25-MGM/sw
Fire protection:	none	KVR M25-MGM
sealable:	No	AST M25
Heavy metals-free:	Yes	KVR M25
PVC-free:	Yes	GMU PA M25
Silicone-free:	Yes	ADR M25
Ingress protection:	IP55 - acc. EN 60529 / DIN VDE 0470-1	WST M25
Weatherproof:	No	WNI M25
Environmental attributes		VST M25
Ambient temperature (min.):	-25 °C	VSS PA M25
Ambient temperature (max.):	40 °C	SNI M25
Ambient temperature (24 h):	35 °C	KS M25
Max. rel. humidity at 25° C (short Therm):	95%	
Max. rel. humidity at 40° C:	50%	