

#### Article

## cle Picture

#### 815.23625B

TERMINAL BLOCK T85 6mmq 450V AC WHITE



| Master data                     |               |  |  |
|---------------------------------|---------------|--|--|
| Minimum order                   | 50 NR         |  |  |
| Net Weight                      | 0.029 KG      |  |  |
| EAN code                        | 8001636113869 |  |  |
| Harmonized System Code (HSCode) | 85369010      |  |  |

| TechData                |                    |  |  |  |
|-------------------------|--------------------|--|--|--|
| Commercial series       | CONNECTO Series    |  |  |  |
| Synthetical description | TERMINAL BLOCK T85 |  |  |  |
| Connecting capacity     | 6mm²               |  |  |  |
| Rated voltage           | 450V               |  |  |  |
| Dimensions              | 120x16,6x17,4mm    |  |  |  |
| Pitch                   | 10mm               |  |  |  |
| Ø fixing hole           | 3,5mm              |  |  |  |
| Colour                  | WHITE              |  |  |  |

### **Approvals and Certifications**



UE Declaration of conformity



I.M.Q. - ENEC 03European Norms Electrical Certification



EAC Eurasian Conformity

| Packaging    |               |  |  |  |
|--------------|---------------|--|--|--|
| Description  | Carton        |  |  |  |
| Quantity     | 400           |  |  |  |
| EAN code     | 8001636535050 |  |  |  |
| Gross weight | 12.8 KG       |  |  |  |

### **Standards and Laws**



CEI EN 60998-1 (1993) [Italian Standard] Connecting devices for low-voltage circuits for household and similar purposes Part 1: General requirements



CEI EN 60998-2-1 (1993) [Italian Standard] Connecting devices for low voltage circuits for household and similar purposesConnecting devices for low voltage circuits for household and similar

voltage circuits for household and similar purposes Part 2-1: Particular requirements for connecting devices as separate entities

### **Annexed**



Technical drawing [DWG]

# WebService:

13/05/2019



| Volume       | 21656.25 CCM     |  |  |
|--------------|------------------|--|--|
| Dimensions   | 275x375x210 (MM) |  |  |
|              |                  |  |  |
| Description  | Box              |  |  |
| Quantity     | 50               |  |  |
| EAN code     | 8001636535043    |  |  |
| Gross weight | 1.6 KG           |  |  |
| Volume       | 2176.2 CCM       |  |  |
| Dimensions   | 130x180x93 (MM)  |  |  |
|              |                  |  |  |





Technical drawing [STP]

|   |  | Note: |  |
|---|--|-------|--|
| > | Max. service temperature - continuous duty: 85°C.                            | x     |  |
| > | Captive screws of zinc-plated steel  | x     |  |
| > | 12 poles   | ×     |  |
| > | Nickel-plated brass terminal   | ×     |  |
| > | Self-extinguishing material in compliance with IEC 60695-2-1 standard 850°C. | x     |  |
| > | Engineering plastic casing   | ×     |  |