

**DIMENSIONS (mm):Φ80*28(Light), 86*40*7(RC)**

Luminair type: LED night light

Finish Colour: transparent+white

Indoor or



Indoor



Outdoor

Market For : EU

Outdoor :

ELECTRICAL DATA:

		RATED	MIN.	MAX.
Rated Wattage	(W) :	2.0		
Rated Voltage	(V) :	4.5		
Input Current	(mA) :	450		
Energy Consumption per 1000h	(kW/h) :	N/A		
Operation power supply:				
For use with power supply type	:	DC(AA*3)		

PHOTOMETRIC DATA:

Luminous Flux	(lm) :	50
Luminous Efficacy	(lm/W) :	25

OPERATING CONDITIONS:

Ta Ambient temperature range	(°C) :	25	10	30
Tc Point	(°C) :	N/A		
IP Degree	:	68		
PBS	:	RG1		
External Control Gear type	:	N/A		
Battery service life	:	Standby: 55 days		

Once a day,30 mins a time: 13 days

Continuous Serving: 5.5 hours

Battery type and number

Alkaline batteries AA*3 for Light, CR2025*1 for RC

Light source

Lighting Brand	:	LED
Light models	:	REFOND
Color temperature	:	5050
Light CRI	:	RGB
Number of lamps	:	N/A
	:	10

Function parameters

	:	Left angle sensor	35°
Sensing range	:	Right angle sensor	35°
	:	RC control distance: ≥7M in the air, about 1.5M under water.	
Sensor type	:	IR	

Luminaire LIFE:

Average Life (L _{70F50})	(h) :	25,000
Switching Cycles	(#) :	50,000

Standards which have to be regarded:

Certifications	:	☒ LVD	☒ EMC	☐ RED
Eye security	:	RG1		
RoHS	:	yes		
REACH	:	yes		

APPLICATION: Suitable for indoor use, like: under cabinet, wardrobe, bookcase...

Issued by : GUANGZHOU
 Date : 17/09/2019
 Revision date :

DATA SHEET

Spec No. : 0053680
 Supersedes :
 Page : 1 of 1