

PRODUCT DATASHEETSMART+ WIFI FLOOD Camera

SMART+ FLOOD CAMERA | Floodlight with integrated camera, speaker, motion and daylight sensor



AREAS OF APPLICATION

- Garages
- Entrance areas
- Outdoor use (IP44)

PRODUCT BENEFITS

- Easy and quick installation
- Increased perception of safety thanks to high brightness

PRODUCT FEATURES

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Luminous flux: 1,800 lm
- Adjustable head
- Type of protection, front side: IP44
- HD Live view camera
- Built in speaker and alarm siren



TECHNICAL DATA


Electrical data

Nominal wattage	24.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz
Operating mode	Mains voltage

Photometrical data

Color temperature	3000 K	
Color rendering index Ra	>80	
Light color (designation)	Warm White	
Luminous flux	1800 lm	

Dimensions & weight



Product weight	990.00 g
Length	163.0 mm
Width	169.0 mm
Height	250.0 mm

Colors & materials

Product color	Dark gray
Body material	Aluminum
Housing color	Dark gray

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Additional product data

Mounting location	Wall
-------------------	------

Mounting type Surface	Mounting type	Surface
-----------------------	---------------	---------

Capabilities

Dimmable Yes		
Type of connection	Terminal, 3-Pole (L, N, PE)	
Compatible smart home technology	Google Assistant / Amazon Alexa	

Certificates & standards

Standards CE/EAC/REACH/RoHS	
Protection class	II
Type of protection	IP44

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075478312	Folding carton box 1	262 mm x 182 mm x 179 mm	1125.00 g	8.54 dm³
4058075478329	Shipping carton box 4	378 mm x 276 mm x 204 mm	4961.00 g	21.28 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.