

Junction Box

Mini 25-L



Mini 25-L

Junction Box

Productnumber: 31090801

Dimensions: 89 x 43 x 38 mm

Junction box acc. to DIN EN 60670 (VDE 0606), 10 entries, 2 floor entries, suitable for confined installation environments such as suspended ceilings and cable ducts, complete with punching tool and blanking plug, with external fixing lugs Accessories supplied: Punching tool and sealing plug

Grey, without terminals, for VDE approved single terminals



Technical Data

electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	400 V
Type of protection:	IP55
Max. conductor cross section:	2,5 mm²
Protection class:	II

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	89 mm
Length:	43 mm
Height:	38 mm

Material characteristics

suitable for exterior use:	no
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	650 °C
Halogen free:	yes
Industry quality:	no

mechanical properties

for sealing range max:	12.5 mm
Type of fastening:	Wall/ceiling mounting
Sealable:	no
for sealing range min:	8.2 mm
Impact strength:	IK07

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Polyethylene
Cover material:	Polypropylene

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
------------	---

Accessories

[30040701 - VST RR - Sealing plugs](#)