



LTE Cat4 Wi-Fi AC1200 Router

Share a high speed 4G LTE mobile broadband network with multiple devices through Wi-Fi or wired connection.

DWR-953V2

- Simply insert your 4G LTE -enable SIM card to share high-speed mobile Internet connection with download speeds of up to 150 Mbps¹
- Enjoy combined Wi-Fi speeds of up to 1200 Mbps² with dual-band wireless AC
- 3 Gigabit Ethernet LAN ports and 1 Gigabit Ethernet WAN/LAN port provide optional wired connectivity
- Fail-safe Internet with concurrent fixed line and mobile Internet support for a reliable and uninterrupted Internet connection
- Two 4G LTE external antenna help achieve optimal network performance



150 Mbps / 50 Mbps

High-speed 4G LTE Internet

Connect with speeds up to 150 Mbps without the need for a fixed-line¹



Gigabit Ethernet Ports

High-speed connections for wired devices and wired broadband.



Dual-Band AC1200

866 Mbps (5 GHz) + 300 Mbps (2.4 GHz) for video streaming, web browsing, social media, and downloading on multiple Wi-Fi devices



SIM Slot Unlocked

Not locked to a specific mobile service provider, allowing you to pick and choose.

Technical Specifications

/ DWR-953V2 LTE Cat4 Wi-Fi AC1200 Router

General

Device Interfaces	1 x 10/100/1000 Gigabit Ethernet WAN/LAN port, 3 x 10/100/1000 Gigabit Ethernet LAN ports, 1 x LTE SIM/USIM Slot, 1 x Reset Button, 1 x WPS Button, 1 x Power Port
LED	Power, Internet, WWAN, 2.4 GHz, 5 GHz, WAN/LAN, SMS, LAN 1-3, Signal Strength
Antenna Type	2 x 2 LTE External Antenna

Functionality

Frequency Support	LTE Bands: FDD:1/3/7/8/20/28 (2100/1800/2600/900/800/700MHz), • TDD: 38/40 (2600/2300MHz) UMTS: 1/8 (2100/900 MHz) GSM/GPRS: Quad-Bands (850/900/1800/1900 MHz)
Data Rates ¹	LTE Downlink: Up to 150 Mbps, LTE Uplink: Up to 50 Mbps DC-HSPA Downlink: Up to 42 Mbps, DC-HSPA Uplink: Up to 5.72 Mbps
Wireless IEEE Standard	IEEE 802.11 ac/n/g/b
Wi-Fi Data Rate ²	5 GHz Up to 866 Mbps, 2.4 GHz Up to 300 Mbps
WAN Interface	PPPoE, static IP, dynamic IP (DHCPclient), PPTP, and L2TP
Security Protocol	64/128-bit WEP (Wired Equivalent Privacy), WPA & WPA2 (Wi-Fi Protected Access)
Firewall	Network Address Translation (NAT), URL Blocking, Stateful Packet Inspection (SPI), MAC Filtering

Software

Device Management	Web UI
-------------------	--------

Physical

Size	154 x 122 x 32 mm
Weight	275 g
Operating Temperature	0 to 40 °C
Storage Temperature	-10 to 70 °C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Certifications	CE , FCC , PTCRB, EMC, Safety , RoHS



¹ Mobile broadband speeds will vary and are dependent on a range of factors including network configuration, network capacity, signal strength, and the conditions of your mobile broadband subscription. A 4G subscription is required in order to achieve maximum speeds. ² Maximum wireless signal rate derived from IEEE Standard 802.11 specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors may adversely affect wireless signal range.