


COMPRESSION CABLE GLANDS POLYAMIDE PA6.6 MAXIBLOCK 1900 SERIES - METRIC THREAD


Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: www.cembre.com - Email: sales@cembre.com

Prepared by: Marketing dept.

MAXIblock® *standard*

Metric thread M 1.5 pitch CEI EN 60423 CEI EN 50262

Ref. Light Grey	P	Fixing Hole Ø (mm)	Ø A mini-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity
1900.M12	M12x1,5	12,2	3,5- 7	15	8	18-22	100
1900.M16	M16x1,5	16,2	5 -10	19	8	22-27	100
1900.M20	M20x1,5	20,5	7 -13	25	9	24-30	100
1900.M25	M25x1,5	25,4	10 -17	30	10	28-39	50
1900.M32	M32x1,5	32,5	13 -21	36	10	33-44	25
1900.M40	M40x1,5	40,5	19 -28	46	10	36-45	15
1900.M50	M50x1,5	50,5	27 -35	55	12	43-52	10
1900.M63	M63x1,5	64,0	34 -45	66	12	45-55	5

Add to Ref: N for Black, G for Dark Grey

MAXIblock® *reduced cable entry*

Metric thread M 1.5 pitch CEI EN 60423 CEI EN 50262

Ref. Light Grey	P	Fixing Hole Ø (mm)	Ø A mini-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity
1910.M12	M12x1,5	12,2	2- 5	15	8	18-22	100
1910.M16	M16x1,5	16,2	3- 7	19	8	22-27	100
1910.M20	M20x1,5	20,5	5-10	25	9	24-30	100
1910.M25	M25x1,5	25,4	7-13	30	10	28-39	50
1910.M32	M32x1,5	32,5	8-14	36	10	33-44	25
1910.M40	M40x1,5	40,5	15-23	46	10	36-45	15
1910.M50	M50x1,5	50,5	21-29	55	12	43-52	10
1910.M63	M63x1,5	64,0	27-39	66	12	45-55	5

Add to Ref: N for Black, G for Dark Grey

MAXIblock® *extended thread*

Metric thread M 1.5 pitch CEI EN 60423 CEI EN 50262

Ref. Light Grey	P	Fixing Hole Ø (mm)	Ø A mini-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity
1901.M12	M12x1,5	12,2	3,5- 7	15	15	18-22	100
1901.M16	M16x1,5	16,2	5 -10	19	15	22-27	100
1901.M20	M20x1,5	20,5	7 -13	25	15	24-30	50
1901.M25	M25x1,5	25,4	10 -17	30	15	30-41	50
1901.M32	M32x1,5	32,5	13 -21	36	15	33-44	25
1901.M40	M40x1,5	40,5	19 -28	46	18	36-45	15
1901.M50	M50x1,5	50,5	27 -35	55	18	43-52	10
1901.M63	M63x1,5	64,0	34 -45	66	18	45-55	5

Add to Ref: N for Black, G for Dark Grey

MAXIblock® *standard factory fitted with locknuts with collar*

Metric thread M 1.5 pitch CEI EN 60423 CEI EN 50262

Ref.	P	Fixing Hole Ø (mm)	Ø A mini-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
1900.M12/X	M12x1,5	12,2	3,5- 7	15	8	18-22	100/10
1900.M16/X	M16x1,5	16,2	5 -10	19	8	22-27	100/10
1900.M20/X	M20x1,5	20,5	7 -13	25	9	24-30	50/10
1900.M25/X	M25x1,5	25,4	10 -17	30	10	28-39	30/10
1900.M32/X	M32x1,5	32,5	13 -21	36	10	33-44	20/10
1900.M40/X	M40x1,5	40,5	19 -28	46	10	36-45	10/5
1900.M50/X	M50x1,5	50,5	27 -35	55	12	43-52	10/5
1900.M63/X	M63x1,5	64,0	34 -45	66	12	45-55	5/5

Light Grey only

Date: 12/07/2018

**COMPRESSION CABLE GLANDS POLYAMIDE PA6.6
MAXIBLOCK 1900 SERIES - METRIC THREAD****Technical details:**

PROTECTION :	IP 68 (EN 60529:1991 / CEI 70-1)
MATERIAL :	POLIAMMIDE 6.6
SEALING RING :	NEOPRENE®
SELF-EXTINGUISHING CLASS :	V2 (UL 94)
TEMPERATURE RANGE :	-20°C ÷ +90°C (continuous) -20°C ÷ +120°C (short period)
GLOW-WIRE TEST (2 mm) :	850°C (EN 60695-2-1/1:1996 / CEI 89-13)
IMPACT CATEGORY :	M12 and M16 M20 ÷ M63
	1 (EN 62444:2013) 3 (EN 62444:2013)
RESISTANCE TO CHEMICALS :	See Annexe A
(R=Resistant; LR= Low Resistance; NR= Not Resistant)	
COLOUR:	RAL 7035 light grey, RAL 9005 black, RAL 7001 dark grey

Marks:**VDE:** *licence Nos 40008472, 4008474, 40008475 e 40008476 (EN 62444:2013)***USL-CNL:** *UL LISTING File No E220310; control No 48SB (UL 514B) valid in USA & Canada***USR-CNR:** **USR-CNR:** *UL RECOGNITION File No E220310 (UL514B) valid in USA & Canada***Markings:**

(EN 62444:2013)

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: www.cembre.com - Email: sales@cembre.com

COMPRESSION CABLE GLANDS POLYAMIDE PA6.6 MAXIBLOCK 1900 SERIES - METRIC THREAD

Annexe A:

Chemical agent	Level of resistance				Note
	Resistant	Limited resistance	Not resistant	Soluble	
Acetaldehyde					Swelling
Acetylene					
Acetone					
Acetic Acid, 30% solution					
Acetic Acid, 5% solution					
Acrylic Acid					
Butyric Acid, aqueous					
Butyric Acid, concentrated					
Citric Acid					
Hydrochloric Acid					
Hydrochloric Acid, concentrated					
Hydrochloric Acid, 40% solution					
Hydrochloric Acid, 1% aqueous solution					
Formic Acid, 10% acid solution					
Formic Acid, 85% acid solution					
Phosphoric Acid, 10% aqueous solution					
Phosphoric Acid, 30 % aqueous solution					
Hydriodic Acid					
Lactic Acid					
Nitric Acid, 1% aqueous solution					
Nitric Acid, 50% aqueous solution					
Oleic Acid (commercial)					
Oxalic Acid, 10% aqueous solution					
Perchloric Acid					
Hydrogen Sulfide					
Hydrogen Sulfide, 10% aqueous solution					
Hydrogen Sulfide, 30% aqueous solution					
Hydrogen Sulfide, 96% aqueous solution					Solvent
Sulfurous Acid					
Tartaric Acid					
Trichloro Acetic Acid					
Water					
Sea Water					
Hydrogen Peroxide, 10 % aqueous solution					Oxidising agent
Allyl Alcohol					
Benzyl Alcohol					
Ethyl Alcohol, concentrated					Swelling
Methyl Alcohol					
Propyl Alcohol					
Alcohols of fatty acid					Swelling
Cinnamic Aldehyde					
Furan Aldehyde					
Zinc Halide, aqueous solution					
Liquid Ammonia					
Carbon Dioxide					
Sulfurous Anhydride					

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: www.cembre.com - Email: sales@cembre.com

COMPRESSION CABLE GLANDS POLYAMIDE PA6.6 MAXIBLOCK 1900 SERIES - METRIC THREAD

Annexe A:

Aniline					
Nitrogen					
Photographic fixing bath					
Ground bacteria (anaerobic)					
Benzaldehyde					
Benzene					
Petrol super grade					
Beer					
Bitumen					
Bromine					
Butanol					
Caprolactam, melted at 75 °C					
Potassium Carbonate, saturated solution					
Zinc Carbonate					
CFC					
Ketone					
Cyclohexane					
Cyclohexanone					
Chloral Hydrate					
Chloramine					
Sodium Chloride, aqueous solution					
Chlorobenzene					
Chloroform					
Calcium Chloride, alcohol solution					
Calcium Chloride, aqueous solution					
Iron Chloride, aqueous acid					
Iron Chloride, neutral, aqueous					
Potassium Chloride, 10% aqueous solution					
Sodium Chloride, saturated solution					
Thionyl Chloride					
Vinyl Chloride					
Fuel for petrol engine					
Creosol					
Dibutyl Phthalate					
Potassium Dichromate					
Diethylene-Glycol					
Dimethylamine					
Dimethylformamide					
Dimethyl Sulfoxide					
Dioxane					
Disinfectant with active chlorine					
Carbon Disulfide					
E 6705					
Heptane					
Benzene Hexachloride					
Hexane					
Ethane					
Ether					
Diethyl Ether					
Ethyl Acetate					
Ethylene					

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: www.cembre.com - Email: sales@cembre.com

COMPRESSION CABLE GLANDS POLYAMIDE PA6.6 MAXIBLOCK 1900 SERIES - METRIC THREAD

Annexe A:

Phenol					Solvent
Fertilizers					
Fluorine					
Brazing flux					Contains: Zinc Halide
Formaldehyde, 10% aqueous solution					
Formamide					See: Dimethylformamide
Phosphate					
Phthalates					Plasticiser
Butane gas					
Chlorine gas					Oxidising agent
Inert gases					
Lighting gas					
Diesel fuel for trucks					
Gel					
Glycerine					
Ethylene Glycol					
Ethylene Glycol					
Grease, wax					
Cattle fat					
Hydrogen					
Calcium Hydroxide, aqueous solution					
Potassium Hydroxide, concentrated & in solution					
Ink					Verify colour absorbtion
Calcium Hypochlorite					
Sodium Hypochlorite					Oxidising agent
Isooctane					
Isopropanol (Isopropyl alcohol)					Swelling
Methane					
Mould					
Ammonium Nitrate, saturated solution					
Silver Nitrate, aqueous solution					
Hydraulic oil					Tests must be performed in operating temperature conditions
Lubricating oil					
Mineral oil					
Gearbox oil					
Fuel oil					
Citrus oil					
Camphor oil					
Colza oil (Rape seed oil)					
Linseed oil					
Fish oil					
Turpentine oil					
Motor oil					
Brake fluid					
Ethylene Oxide					

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: www.cembre.com - Email: sales@cembre.com

COMPRESSION CABLE GLANDS POLYAMIDE PA6.6 MAXIBLOCK 1900 SERIES - METRIC THREAD

Annexe A:

Oxygen					At 3 bar
Ozone, 20 ppm					Oxidising agent
Paraffin					
Potassium Perchlorate , 2% aqueous solution					Oxidising agent
Potassium Permanganate, 10% aqueous solution					Oxidising agent
Petroleum					
Natural Petroleum Gas					
Propane					
Cellulose covering					
Blood					
Silicon fluid					
Caustic soda, 10% aqueous solution					
Caustic soda, concentrated aqueous solution					See: Potassium Hydroxide , solution
Soda, aqueous solution					
Soda, saturated solution					
Sodium Trisulfate, solution 200g/l					
Ammonium Sulfate, saturated solution					
Copper Sulfate, saturated solution					
Sodium Sulfide, saturated solution					
Agfa processing solution					
Photographic processing solution					
Sweet solution pH 4.5					
Sweet solution pH 9.5					
Solvent for dry wash with boiling point between 100-140 °C					
Styrene					
Fruit juice					
Carbon Tetrachloride					
Carbon Tetrafluoride					
Tincture of Iodine (commercial)					
Toluene					
Trichloroethylene					
Triethanolamine					
Urea, 20% aqueous solution					
Urine					
Water vapour					
Xylene					
Sugar, saturated solution					

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: www.cembre.com - Email: sales@cembre.com