

thePrema P360 KNX AP Multi WH

Item no.: 2079900



Home and Building control
KNX

Description

- Multi-sensor KNX
- Consisting of passive infra-red presence detector KNX and air quality sensor KNX (= 2 bus participants)
- Functions air quality sensor:
 - Measures CO₂ level, relative humidity, temperature and barometric air pressure
 - Three independent, configurable thresholds for the CO₂ level and relative humidity
- Integrated individual room thermostat
- 4 binary inputs
- Functions presence detector:
 - Square detection area 360°, 9 x 9 m, (81 m²) at mounting height 3 m
 - 3 channels light and 2 channels presence
 - 2 channel light C1, C2 with 2 light measurements and additional lighting channel C3 without brightness factor
 - 2 presence channels can be set individually
 - Adaptable 3 channel light measurement
 - Mixed light measurement suitable for LEDs, fluorescent lamps (FL/PL/ESL) and halogen/incandescent lamps
 - Can be used as fully or semi-automatic, switchable
 - Switch or constant light control mode with stand-by function
 - Dimmable lighting in switch mode with stand-by function
 - Brightness switching value or set point value can be set in lux using parameters, on the device itself or via remote control
 - Teaching in of the brightness switching value or the set point value
 - Room correction factor setting for brightness measurement calibration
 - Light time delay can be set using parameters, on the device itself or via remote control
 - Switch on delay and time delay for presence can be set
 - Detection sensitivity can be set
 - Self-learning time delay
 - Reduced time delay in the event of a shorter stay in the room (short presence)
- Scenario functions
- Extremely easy setting of energy saving characteristics with the new "eco plus" function
- Test mode for checking function and detection range
- Parallel switching of several detectors in Master/Slave or Master/Master possible
- User remote control and management-remote control (optional)
- Room monitoring
- * According to warranty terms and conditions, see www.theben.de/en/guarantee



Subject to technical changes and misprints

additional information at: www.theben.de/product/2079900

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

thePrema P360 KNX AP Multi WH

Item no.: 2079900



theben

Technical data

thePrema P360 KNX AP Multi WH		thePrema P360 KNX AP Multi WH	
Installation height	2 – 10 m	Ambient temperature	5°C ... 40°C
Minimum height	> 1,7 m	Detection range	81 m ² (9,0 x 9,0 m)
Measuring range brightness	5 – 3000 lx	Colour	White
Detection angle	360°	Measuring range CO ₂	300 – 5000 ppm
Installation type	Ceiling installation	Setting range temperature	-5°C ... 45°C
Light switch-off delay	30 s – 60 min / inaktiv / ein	Measuring range air pressure	30000 – 110000 Pa
Lamps	Energy saving lamps, fluorescent lamps, Incandescent / halogen lamps, LEDs	Measuring range humidity	1 – 100 % rH
Light measurement	Mixed light measurement	Interface extension max.	30 m
Presence switch-off delay	10 s – 120 min	Type of protection	IP 20
Switch-on delay presence	10 s – 30 min / inactive		

Detection range for planning applications at a temperature of 21 °C

Mounting height (A)	Sitting (S)	Walking (T)
2 m	20 m ² 4.5 m x 4.5 m	36 m ² 6 m x 6 m ± 0.5 m
2.5 m	36 m ² 6 m x 6 m	64 m ² 8 m x 8 m ± 0.5 m
3 m	49 m ² 7 m x 7 m	81 m ² 9 m x 9 m ± 1 m
3.5 m	64 m ² 8 m x 8 m	100 m ² 10 m x 10 m ± 1 m
5 m		144 m ² 12 m x 12 m ± 1.5 m
10 m		400 m ² 20 m x 20 m ± 2 m



Detection range according to Sensnorm IEC 63180

Mounting height (A)	Diagonally (T)	Head on to (R)	Sitting (S)
---------------------	----------------	----------------	-------------

Subject to technical changes and misprints

additional information at: www.theben.de/product/2079900

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

04/06/2023


Page 2 of 3

thePrema P360 KNX AP Multi WH

Item no.: 2079900

theben

Scale drawings



Accessories

theSenda P

Item no.: 9070910




theSenda S

Item no.: 9070911



QuickSafe

Item no.: 9070531



theSenda B

Item no.: 9070985



Subject to technical changes and misprints

additional information at: www.theben.de/product/2079900

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

04/06/2023

Page 3 of 3