



PLUG, IN POLYAMIDE PA6, METRIC PITCH, IP54



Features

TECHNICAL INFORMATION

Minimum operating temperature	-20 °C
Maximum operating temperature	90 °C
Threshold of operating temperature for short periods	110 °C
Ingress Protection	IP54
Markings found	factory mark; thread type
Reference standard	CEI EN 60423
Self-extinguishing fire class according to UL 94	HB

LOGISTIC


Type of packaging	; box
Customs code	39269097

MATERIAL COMPOSITION AND TREATMENTS

Material	Polyamide 6
Halogen free	No

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Plug for cable screw gland [EC000032]
--------------	---------------------------------------



1053

tipo	P	Color	C [mm]	Fixing hole diameter [mm]	Width [mm]	H [mm]	Gross weight [g]	Unit in standard packaging [pcs]	Minimum order quantity [pcs]
1053M12	M12x1,5	Grey RAL 7035	6	12.2	15	8	0,874	100	100
1053M12N	M12x1,5	Black RAL 9005	6	12.2	15	8	0,860	100	100
1053M16	M16x1,5	Grey RAL 7035	6	16.2	20	9	1,617	100	100
1053M16N	M16x1,5	Black RAL 9005	6	16.2	20	9	1,620	100	100
1053M20	M20x1,5	Grey RAL 7035	7	20.5	25	10	2,700	100	100
1053M20N	M20x1,5	Black RAL 9005	7	20.5	25	10	2,780	100	100
1053M25	M25x1,5	Grey RAL 7035	7	25.4	30	10	3,535	100	100
1053M25N	M25x1,5	Black RAL 9005	7	25.4	30	10	3,580	100	100
1053M32	M32x1,5	Grey RAL 7035	9	32.5	37	12	5,280	50	50
1053M32N	M32x1,5	Black RAL 9005	9	32.5	37	12	5,680	50	50
1053M40	M40x1,5	Grey RAL 7035	9	40.5	47	13	8,883	30	30
1053M40N	M40x1,5	Black RAL 9005	9	40.5	47	13	9,467	30	30
1053M50	M50x1,5	Grey RAL 7035	10	50.5	58	15	14,645	20	20
1053M50N	M50x1,5	Black RAL 9005	10	50.5	58	15	15,800	20	20
1053M63	M63x1,5	Grey RAL 7035	12	64	72	18	27,000	10	10
1053M63N	M63x1,5	Black RAL 9005	12	64	72	18	26,290	10	10